

/TestCloud/DevOps/Product/list	
GET	获取 Product 的列表
Response	<pre>{ "ErrorCode": 1000, "Description": "OK", "TotalCount": 2, "ProductList": [{ "ProductID": 1, "ProductName": "UShop" }, { "ProductID": 2, "ProductName": "RMM" }] }</pre>
/TestCloud/DevOps/Plan/list	
GET	获取某个 Product 下对应的 DevOpsPlan 的 list
Parameter	ProductID
	<pre>{ "ErrorCode": 1000, "Description": "OK", "TotalCount": 2, "PlanList": [{ "DevOpsPlanID": 1, "PlanName": "UShopApi", }, { "DevOpsPlanID": 2, "PlanName": "UShopMsgPro", }] }</pre>

/TestCloud/DevOps/Build/list	
GET	获取某个 DevOpsPlan 下对应的 Build list
Parameter	DevOpsPlanID
Response	<pre> { "ErrorCode": 1000, "Description": "OK", "TotalCount": 2, "BuildList": [{ "BuildIndex": 1, "Status": "Pass", "StartTime": 1491904800 }, { "BuildIndex": 2, "Status": "Fail", "StartTime": 1491904800 }] } </pre>
/TestCloud/DevOps/Build/add	
POST	添加一个 Build
Request	<pre> { "DevOpsPlanID": 1 "JobName": "Test", "Parameter": { "parameter": [{ "name": "DevOpsPlanID", "value": "1" }, { "name": "BuildIndex", "value": "1" }] } } </pre>

Response	<pre>{ "ErrorCode": 1000, "Description": "OK", "BuildIndex": 1 }</pre>
/TestCloud/DevOps/Stage/info	
GET	获取某个 Build 对应的 Stage
Parameter	<p>DevOpsPlanID</p> <p>BuildIndex</p>
Response	<pre>{ "ErrorCode": 1000, "Description": "OK", "StageCount": 2, "StageList": [{ "StageID": 1, "StageName": "", "PreStageID": ["1"], "Status": "Pass", "Detail": {}, "StartTime": 1400000, "EndTime": 1400000 }, { "StageID": 2, "StageName": "", "PreStageID": [1], "Status": "Fail", "Detail": {}, "StartTime": 1400000, "EndTime": 1400000 }] }</pre>
/TestCloud/DevOps/Build/update	
POST	修改某个 Build 的状态

Request	<pre>{ "DevOpsPlanID": 1, "BuildIndex": 1, "StageName": "Build", "Status": "running", "Detail": {"URL": "http://**"} }</pre>
Response	<pre>{ "ErrorCode": 1000, "Description": "OK" }</pre>